



DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No. 305/2011

Name of the product :

CONTROLL® INNERSEAL PLUS⁺

No.: CI 003

1. Unique identification code of the product-type:

EN 1504-2: ZA.1b/ZA.1c.

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) of the CPR:

Batch number: See on product labelling.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

EN 1504-2

Surface Protection Products - Impregnation

- Ingress protection (1.2)

- Physical resistance (5.2)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

MAYNOR AS

STOREBOTN, 5300 KLEPPESTO

NORWAY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (NPD)

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+ (for uses in buildings and civil engineering works)

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 1504-2 : 2004, System 2+

The notified certification body KONTROLLRÅDET identification number 1111 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:

Certificate of conformity of the factory production control

No: 1111-CPD-0556

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant (NPD)

9. Declared performance:


Table 4: Performance for Impregnation:

| Essential Characteristics | Performance | Harmonized Technical Specification |
|---|--|------------------------------------|
| ABRASION RESISTANCE | > 30 % | EN 1504-2:2004 |
| PERMEABILITY TO WATER VAPOUR | NPD | |
| CAPILLARY ABSORPTION PERMEABILITY TO WATER | W < 0,1 kg/m ² h ^{0,5} W < 0,1 kg/m ² h ^{0,5} | |
| THERMAL COMPABILITY | NPD | |
| CHEMICAL RESISTANCE | NO VISUAL EFFECTS | |
| IMPACT RESISTANCE | CLASS III: > 20 NM | |
| ADHESION STRENGTH (pull off) | 3,0 N/mm ² | |
| REACTION TO FIRE | EUROCLASS A1 (INCOMBUSTIBLE) | |
| SLIP/SKID RESISTANCE | NPD | |
| DEPTH OF PENETRATION | CLASS II >10 mm (16 mm) | |
| DANGEROUS SUBSTANCES COMPLY WITH 5.3 | NO SPEC. PRECAUTIONS REQUIRED | |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Bergen, Norway April 07. 2014

Place and date of issue



General manager Maynor AS