

**COVERAGE:**

0.4-0.8 l/m<sup>2</sup> depending on the absorptive capacity of the substrate.

**DRYING TIME:**

Touch dry within 1 hour.  
Dry after 12 hours.

**APPEARANCE:**

Bluewhite liquid

**pH:**

8-9

**DENSITY:**

1.1 g/cm<sup>3</sup>

**FREEZING POINT:**

0° C

**FIRE:**

Non-flammable

**PACKAGING:**

20 litre/ 1000 litre

**STORAGE/SHELF-LIFE:**

Cool, dark / > 36 months

**CLEANING:**

Tools: Water

Skin: Soap and water



# DustBond

Prevents dusting from concrete

**DESCRIPTION:**

Controll®DustBond is an environmentally and user-friendly product for preventing powdery dust from spreading from old and new surfaces – especially brick walls. It creates a smooth transparent surface that is easy to keep clean. Controll®DustBond hardens to a film that is both water-resistant and permeable. The product contains no solvents and is non-flammable.

**TYPICAL APPLICATIONS:**

- Brick
- Walls
- Garages
- Ceilings
- Plastering
- Facades
- Indoor fireplaces
- Sandstone

**PRODUCT HIGHLIGHTS:**

The water-based binder allows the surface to breathe and one application will leave a transparent surface.

The product is odourless and the treated area can be used as soon as the surface is dry, usually within 30 minutes. Application is very simple and does not represent any health or fire hazard.

The final result provides an inexpensive surface that is easy to clean and maintain.

**PREPARATIONS:**

The surface to be treated must be cleaned, free of paint, grease or any other coating that may obstruct the substrate's absorption. Protect glass, aluminium and other polished or painted surfaces to prevent staining. The temperature during application and for the following 24 hours must be between 5°C and 40°C.

**DIRECTIONS FOR USE:**

The product is ready for use and can not be mixed with other liquids or diluted.

Apply with a low-pressure sprayer until full coverage is attained.

In case of spills, flush immediately with water.

**MANUFACTURER:**

BETONGTETT AS  
Storebotn 13 D  
5309 Kleppesto  
NORWAY

E-mail:  
Phone:

[www.innerseal.eu](http://www.innerseal.eu)  
[service@innerseal.eu](mailto:service@innerseal.eu)  
+47 46 17 17 00